

# CRAYVALLAC® WN-1150

Modified polyethylene matting agent for powder coatings  
**Micronised wax**

## TYPICAL CHARACTERISTICS

Nature	<b>Special wax</b>
Appearance	<b>Off-white micronized powder</b>
Active Content (%)	<b>100</b>

## DESCRIPTION

CRAYVALLAC® WN-1150 is used to control gloss between 30 – 60% for epoxy/polyester hybrid, HAA and TGIC based polyester powder coatings. No effect on weather ability or physical properties.

## RECOMMENDED ADDITION LEVEL

1.0 - 6.0%

## STANDARD PACKAGING

Other packaging may be available upon request

- 15 Kg Bag

## HANDLING & STORAGE

It should be stored in the original containers in a dry place at temperatures between 5°C (41°F) and 30°C (86°F). Avoid exposure to direct sunlight or frost. In these conditions, this product should be used within 48 months from production.

## PROCESSING INSTRUCTIONS

Simple dispersion and blending with other powder components.

## HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

## MARKET

- Coatings & Inks**
- Graphic Arts
  - Industrial Coating

## KEY BENEFITS

### FORMULATION

- **Ready to use**
- **Easy handling**



### FILM PROPERTIES

- **Matting effect**



- **APEO free**
- **Bacteria resistance**
- **Heavy metal free**
- **Solvent-free**

**Yes**  
**Yes**  
**Yes**  
**Yes**