RHEOCOAT™ 2121

Rheology modifier for curtain coating

TYPICAL CHARACTERISTICS

Nature Anionic polymer in emulsion

Appearance Viscous liquid

Solid Content (%) 37.5 pH 7
Brookfield viscosity (mPa.s) 300 Specific gravity 1.05

DESCRIPTION

Rheocoat™ 2121 is an anionic polymer allowing a better control of the curtain coating rheology.

RECOMMENDED ADDITION LEVEL

0.05 to 0.5 as received

STANDARD PACKAGING

Other packaging may be available upon request

• 1000L IBC

HANDLING & STORAGE

Emulsion must be stored inside a building at a constant temperature between 5°C and 30°C. During thestorafe and handling, the emulsion must not be contaminated by water. Emulsions must be stirred before use as it can separate.

Effect of cycles of warm and cold temperatures

The observations are called raincycle. A container of emulsion initially at a temperature of 20°C in a warehouse, is placed, for several hours outside where the temperature is 5°C. The water vapor contained in the free volume above the product condenses and drops of water formed on the roof of the container fall down on the surface of the emulsion, creating local coagulations. Gel formed looks like white stringy lumps floating on the surface or suspended to the cover of the drum or container.

In these conditions, this product should be used within 3 months from delivery.

PROCESSING INSTRUCTIONS

Shall be introduced at the end of the coating color preparation after the pigments and the binders and prior to the pH adjustment with a diluted caustic soda.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKET

Pulp & Paper

Board CoatingBoard Coating

KEY BENEFITS

- Precoat
- Topcoat
- Contribution to brookfield viscosity
- Contribution to high shear viscosity
- Water retention



2024-04-16 Page 1/