# **TOPSPERSE™ CX L**

Dispersing agent for paper coating colors

#### **TYPICAL CHARACTERISTICS**

Nature Appearance Solid Content (%) pH Brookfield viscosity (mPa.s) Specific gravity Sodium polyacrylate Liquid, colour less to slightly yellow 45 8 1070 1.33

#### DESCRIPTION

Topsperse™ CX L is an acrylic polymer specially designed for aqueous dispersion of kaolin and calcium carbonate. Topsperse™ CX L provides stable high solids slurries. Topsperse™ CX L contributes to reduce costs and to improve flexibility of Coating Color formulations.

#### **RECOMMENDED ADDITION LEVEL**

0.2 to 0.5 parts d/d

#### **STANDARD PACKAGING**

Other packaging may be available upon request

- 1000L IBC
- Bulk

#### **HANDLING & STORAGE**

The product should be protected from the effects of weathering, stored between 5 and 40°C and protected from sun exposure. Once opened, packaging should be resealed immediately after use.

In these conditions, this product should be used within 12 months from delivery.

#### HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

## MARKET

### Pulp & Paper

- Board Coating
   Board Coating
- Paper Coating
- Paper Coating

#### **KEY BENEFITS**

MINERALS SUSPENSION
• Clay

\_\_\_\_\_

MINERAL PARTICLE SIZE
• Coarse

2024-04-24 Page 1/



Contact us to know more about our additives <a href="http://www.RheologySpecialtyAdditives.com">www.RheologySpecialtyAdditives.com</a>

ARKEMA