

Acrylic associative thickener for water-based systems

HASE Acrylic Thickener

Typical Characteristics

Nature	Aqueous dispersion of an acrylic copolymer
Appearance	Low viscous white milky liquid
Solid Content (%)	26
Active Content (%)	26
pH	3
Specific gravity	1.05
Solvent	Water

Description

Rheotech™ M 326 is a highly effective associative acrylic thickener especially designed for water-based putties and textured coating formulations. Rheotech™ M 326 provides high viscosities at low and medium shear rate with a good shear thinning behaviour. It is therefore giving a good body and high build to formulations while exhibiting ease of application.

Standard Packaging

Other packaging may be available upon request

- 1000L IBC
- 200L Drum
- Bulk

Handling & Storage

It can be irreversibly altered by frost. It should be protected from the effects of weathering and stored between 5 and 40°C and protected from direct sun exposure. Once opened, packaging should be resealed immediately after use. In these conditions, this product should be used within 6 months from delivery.

Health and environmental data

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

Adhesives & Sealants

- Assembly
- Other Adhesives
- Sealants

Coatings & Inks

- Architectural Coating

Key Benefits

Formulation

- Cost in use
- Compatibility
- Easy handling

Storage

- Antisettling
- In-can appearance
- Syneresis resistance

Application

- Brushability
- Rollability
- Sag resistance

Film Properties

- Hiding power/Opacity
- Rub out
- Stain resistance

Thickening mechanism

Non Associative
Self Association
Associative



Viscosity contribution

Low Shear contribution ●●●●●
Mid Shear contribution ●●●●○
High Shear contribution ●○○○○

PVC

PVC Low
PVC Mid
PVC High

